

**CP- UNC-TE20ZL5-MD****2 MP Full HD WDR IP IR Bullet Camera - 50 Mtr.****Main Features**

- 1/2.7" 2Megapixel PS CMOS Image Sensor
- H.264 & MJPEG dual-stream encoding
- Max 25/30fps@1080P(1920×1080)
- WDR(120dB), Day/Night(ICR), 3D-DNR, AWB, AGC, BLC
- IR Range of 50 Mtrs.
- 2.7mm ~12mm motorized lens
- Supports PoE, IP67, Micro SD Card
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



# CP- UNC-TE20ZL5-MD

## 2 MP Full HD WDR IP IR Bullet Camera - 50 Mtr.

### Feature

Image Sensor  
 Minimum Illumination  
 Shutter Speed  
 White Balance  
 Gain Control(AGC)  
 Lens  
 Video Compression  
 S/N Ratio  
 Back Light Compensation  
 Video Streaming  
 Resolution  
 Privacy Mask  
 ICR  
 Audio Input  
 Audio Compression  
 Audio Output  
 Alarm IN  
 Alarm Out  
 Protocol  
 Smart Detection  
 Ethernet  
 User Account  
 IR  
 Smart Phone  
 Micro SD  
 Operating Temperature  
 Power Source  
 Power Consumption  
 Weatherproof Standard  
 Regulatory  
 Dimension  
 Weight

### Specification

1/2.7" 2 Megapixel CMOS  
 0.01Lux/F1.4(Color); 0Lux/F1.4(IR on)  
 Auto/Manual, 1/3(4)~1/10000s  
 Auto/Manual  
 Auto/Manual  
 2.7mm~12mm Motorized  
 H.264/MJPEG  
 More than 50 dB  
 BLC / HLC / WDR(120dB)  
 Main Stream:1080P/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)  
 1080P(1920×1080)/720P(1280×720)/D1(704×576)/CIF(352×288)  
 Up to 4 areas  
 Auto(ICR)/Color/B/W  
 1 Ch.  
 G.711a/ G.711u/ AAC  
 1 Ch.  
 2 Ch.  
 1 Ch.  
 IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S  
 Tripwire, Intrusion, Scene Change, Face Detect  
 RJ-45 (10/100Base-T)  
 20 users  
 IR Range of 50 Mtr.  
 iPhone, iPad, Android, Windows Phone  
 Micro SD, Max 128GB  
 -20°C~+60°C, Less than 90% RH  
 DC12V, PoE(802.3af)  
 <11.5W (with IR on, motorized lens working)  
 IP67  
 CE, FCC and RoHS  
 272.9 mm × 94.9mm× 94.9mm  
 1.1kg

