


CP- UNP-2020SL10

2MP Full HD IP PTZ Camera



Main Features

- 1/2.8" CMOS Image sensor
- Powerful 20x Optical and 16x Digital zoom
- DWDR, Day/Night(ICR), Ultra DNR
- Up to 255 Presets, 8 Tour, 5 Pattern, 5 Auto scan
- Max 240°/s pan speed, 360° endless pan rotation
- IR Range of 100 Mtr.
- Built-in 2/1 alarm in/out, IP66
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro, vOptimus Pro



CP- UNP-2020SL10

2MP Full HD IP PTZ Camera

Feature

Image Sensor
 Effective Pixels
 Video Output
 S/N Ratio
 Minimum Illumination
 Focal Length
 Focus Control
 White Balance
 Angle of View
 Close Focus Distance
 Electronic Shutter
 AGC control
 Back Light Compensation
 Optical Zoom
 Digital Zoom
 Pan Travel
 Tilt Travel
 Presets
 Preset Speed
 Privacy Masking
 Special Features
 Power up Action
 Idle Motion
 Day/Night: IR Cut Filter
 Video Compression
 Video Streaming
 Audio Compression
 Audio Streaming

 Protocols

 Alarm

Specification

1/2.8" CMOS
 1920(H) x 1080(V), 2 Megapixels
 BNC(1.0Vp-p/75Ω), PAL / NTSC
 More than 50dB
 Color: 0.05Lux@F1.4, B/W: 0.005Lux@F1.4
 4.7mm~94mm
 Auto / Manual
 Auto, ATW, Indoor, Outdoor, Manual
 H: 54.1° ~ 3.2°
 100mm~ 1000mm
 1/1 ~ 1/30,000s
 Auto / Manual
 BLC / HLC / DWDR
 20x
 16x
 360° endless, Pan Speed: 0.1° ~ 160°/sec
 -15° ~ 90°, Tilt Speed: 0.1° ~ 120°/sec
 255
 Pan: 240° /s; Tilt: 200° /s
 Up to 24 areas
 IR Range upto 100m, Up to 255 Presets, 8 Tour, 5 Pattern, 5 Auto scan
 Auto restore to previous PTZ and lens status after power failure
 Activate Preset/ Pan/ Scan/ Tour/ Pattern if there is no command in the specified period
 Auto(ICR) / Color / B/W
 H.264 / MJPEG
 Main Stream: 25/30fps@1080P/720P, Sub Stream: 25/30fps@D1/CIF
 G.711a / G.711u(32kbps)/ PCM(128kbps)
 1/1 channel In/Out

 IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S

 2/1 channel In/Out



CP- UNP-2020SL10
2MP Full HD IP PTZ Camera

Feature

Max Remote Users
Operating Temperature
Memory Slot
Smart Phone
Weather Proof Standard
Dimension
Weight
Power Source
Power Consumption

Specification

20 users
-40°C ~ 60°C / Less than 90% RH
Micro SD, Max 64GB
iPhone, iPad, Android, Windows Phone
IP66
Φ204.7(mm) x 359.9(mm)
7.8kg
AC 24V/5A
10.5W, 26W (IR on, Heater on)