

CP- UNR-404T1-P4

4 Ch. Network Video Recorder with 4 PoE Ports



Main Features

- 4 Ch. with 1080p Realtime Live View
- H.264/MJPEG dual codec decoding
- Up to 5Mp resolution preview&playback
- Max 80Mbps incoming bandwidth
- Support 1 SATA HDDs up to 4TB, 2 USB2.0
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.3 conformance, 4 Ports PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS, KVMS Pro



CP- UNR-404T1-P4

4 Ch. Network Video Recorder with 4 PoE Ports

Feature

Processor
 Operating System
 IP Camera Input
 Two-way Talk
 User Interface
 Video Output
 Compression
 Video Resolution
 Video Recording
 Video Display Split
 Motion Detection
 Video Loss
 Camera Blank
 Smart Phone
 Hard Disk
 Trigger Events
 Recording Mode
 Search Mode
 Playback
 Backup Mode
 Interface Ports
 Record Interval
 Max User Account
 Ethernet
 Protocols
 Power Supply
 Power Consumption
 Working Temp
 Dimensions
 Weight

Specification

Dual-core embedded processor
 Embedded LINUX
 4 channel
 1 channel Input, 1 channel Output, RCA
 GUI
 1 HDMI, 1 VGA
 H.264 / MJPEG
 2560×1920, 2048×1536, 1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768
 Max 80 Mbps
 1/4
 MD Zones: 396(22×18).
 Supports
 Supports
 iPhone, iPad, Android, Windows Phone
 1 SATA ports, up to 8TB
 Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen
 Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
 Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
 USB Device / Internal SATA burner/ Network
 1 HDMI, 1 VGA, 2 USB2.0, 1 RJ45
 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
 128 users
 1 RJ-45 port (10/100M/1000M)
 HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.3
 DC12V/2A
 NVR: 10W(without HDD), PoE: Max 25.5W for single port
 -10 ~+55°C / 10~90%RH / 86~106kpa
 325mm × 240mm × 45mm
 1.25 Kg (without HDD)